

### **MODEL HX4210**

100MHz 10x Frequency Divider ULTRA LOW PHASE NOISE

- 100MHz Input, 10MHz Output
- +10dBm Input / Output
- -170 dBc/Hz Additive Phase Noise
- DC Supply: 8V<sub>DC</sub> to 12V<sub>DC</sub> (100mA)
- Integrated Low Noise Bias Network



#### **SUMMARY**

The Holzworth HX4210 100MHz 10x Frequency Divider is a high grade laboratory accessory. An emphasis was placed on maintaining the low jitter and phase noise of an external reference or frequency source to maintain the integrity of system timing and noise.

The HX4210 Frequency Divider is a laboratory grade reference divider that has a high output power and will operate with a broad range of power supplies. Holzworth products are 100% final performance tested for phase noise verification<sup>1</sup>.

#### **SPECIFICATIONS** <sup>2</sup> PRELIMINARY

PARAMETER	MIN	TYP	MAX	UNITS	COMMENTS	
Input Frequency	90	100	110	MHz	50 ohms	
Output Frequency	9	10	11	MHz	50 ohms	
Input Power	5	10	15	dBm	50 ohms	
Output Power	9	11	13	dBm	50 ohms	
Phase Noise (Additive)		-170		dBc/Hz	Output Referred (100MHz Input)	
Output Harmonics 2 <sup>nd</sup> Harmonic 3 <sup>rd</sup> Harmonic		-40 -60	-30 -30	dBc dBc	10MHz ±2MHz 10MHz ±2MHz	
Spurious Output		-70		dBc		
DC Supply	8		12	V <sub>DC</sub>	±10%, 50mA	
RF Connectors	SMA Jack (female)					
DC Connector	SMA Jack (female)					
Housing Dimensions (LxWxH)	1.75" x 1	.5" x 0.5"	(44.5mm	(44.5mm x 38.1mm x 12.7mm)		

 $<sup>^{1}</sup>$  Final performance verification at RF<sub>INPUT</sub>= 100MHz / +10dBm, RF<sub>OUTPUT</sub>= 10MHz, Residual Setup

### **RoHS Compliant**

HOLZWORTH INSTRUMENTATION, INC BOULDER, COLORADO

Email: sales@holzworth.com

HX4210 Aug 2018

<sup>&</sup>lt;sup>2</sup> Specifications are subject to change per the discretion of Holzworth Instrumentation, Inc.



# **MODEL HX4210**

100MHz 10x Frequency Divider ULTRA LOW PHASE NOISE

#### **HX4210 PERFORMANCE DATA**

The phase noise data provided here demonstrates typical performance of the HX4210 100MHz 10x Frequency Divider under ambient laboratory conditions. Refer to Figure 1 for phase noise data and Figure 2 for a diagram of the test setup.





Figure 1: HX4210 Phase Noise Data



**Figure 2: Phase Noise Test Setup** 

HOLZWORTH INSTRUMENTATION, INC BOULDER, COLORADO

Email: sales@holzworth.com




## **MODEL HX4210**

100MHz 10x Frequency Divider ULTRA LOW PHASE NOISE

#### **MECHANICAL**

The HX4210 Frequency Divider comes in a compact, shielded housing complete with mounting holes for ease of system integration into various applications. Mechanical dimensions are listed in both inches and (mm). Tolerances are to within ±0.010 inches.



## **RoHS Compliant**

#### **WARRANTY**

All Holzworth frequency dividers come with a 1 year 100% product warranty covering manufacturing defects. All product repairs and maintenance must be performed by Holzworth Instrumentation. Holzworth reserves the right to invalidate the warranty for any product that has been tampered with or used improperly. Refer to Holzworth Terms & Conditions of Sales for more details.

HOLZWORTH INSTRUMENTATION, INC BOULDER, COLORADO

Email: sales@holzworth.com